

# **ALPI GREEN POL RECT 120X260**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A036941** 120X260 5,60 PC BIA GL



#### **DIMENSIONS AND SURFACE PROPERTIES**

| PHYSICAL PROPERTIES                  |                 |                        |
|--------------------------------------|-----------------|------------------------|
| Water absorption capacity            | EN ISO 10545-03 | < 0,5%                 |
| Flexion resistance                   | EN ISO 10545-04 | $=> 50 \text{ N/mm}^2$ |
| Deep abrasion resistance             | EN ISO 10545-06 | 175                    |
| Abrasion resistance (glazed Ceramic) | EN ISO10545-07  | 0.00                   |
| Thermal shock resistance             | EN ISO 10545-09 | It stands the test     |
| Cracking resistance                  | EN ISO 10545-11 | It stands the test     |
| Frost resistance                     | EN ISO 10545-12 | It stands the test     |

| CHEMICAL PROPERTIES                                    |                 |     |  |
|--|-----------------|-----|--|
| Resistance to acids                                    | EN ISO 10545-13 | ULB |  |
| Resistance to alcalis                                  | EN ISO 10545-13 | ULB |  |
| Resistance to cleaning products                        | EN ISO 10545-13 | UA  |  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | UA  |  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |  |









# **ALPI GREEN POL RECT 60X120**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A039282** 60x120 10,40 PC BIA GL



#### **DIMENSIONS AND SURFACE PROPERTIES**

|                                      | PHYSICAL PROPERTIES |                         |
|--------------------------------------|---------------------|-------------------------|
| Water absorption capacity            | EN ISO 10545-03     | < 0,5%                  |
| Flexion resistance                   | EN ISO 10545-04     | => 45 N/mm <sup>2</sup> |
| Abrasion resistance (glazed Ceramic) | EN ISO10545-07      | IV                      |
| Thermal shock resistance             | EN ISO 10545-09     | It stands the test      |
| Cracking resistance                  | EN ISO 10545-11     | It stands the test      |
| Frost resistance                     | EN ISO 10545-12     | It stands the test      |

| CHEMICAL PROPERTIES                                    |                 |     |
|--|-----------------|-----|
| Resistance to acids                                    | EN ISO 10545-13 | GLA |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLA |
| Resistance to cleaning products                        | EN ISO 10545-13 | GA  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |









# **ALPI GREEN POL RECT 60X60**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A039581** 60X60 9,50 PC BIA GL



#### **DIMENSIONS AND SURFACE PROPERTIES**

| DH                                   | YSICAL PROPERTIES |                         |
|--------------------------------------|-------------------|-------------------------|
| 711                                  | TOTORE PROPERTIES |                         |
| Water absorption capacity            | EN ISO 10545-03   | < 0,5%                  |
| Flexion resistance                   | EN ISO 10545-04   | => 45 N/mm <sup>2</sup> |
| Abrasion resistance (glazed Ceramic) | EN ISO10545-07    | IV                      |
| Thermal shock resistance             | EN ISO 10545-09   | It stands the test      |
| Cracking resistance                  | EN ISO 10545-11   | It stands the test      |
| Frost resistance                     | EN ISO 10545-12   | It stands the test      |
|                                      |                   |                         |

| CHEMICAL PROPERTIES                                    |                 |     |  |
|--|-----------------|-----|--|
| Resistance to acids                                    | EN ISO 10545-13 | GLA |  |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLA |  |
| Resistance to cleaning products                        | EN ISO 10545-13 | GA  |  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA  |  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |  |









# **ALPI GREEN POL RECT 30X60**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A039582** 30X60 10,00 PC BIA GL



#### **DIMENSIONS AND SURFACE PROPERTIES**

| DH                                   | YSICAL PROPERTIES |                         |
|--------------------------------------|-------------------|-------------------------|
| 711                                  | TOTORE PROPERTIES |                         |
| Water absorption capacity            | EN ISO 10545-03   | < 0,5%                  |
| Flexion resistance                   | EN ISO 10545-04   | => 45 N/mm <sup>2</sup> |
| Abrasion resistance (glazed Ceramic) | EN ISO10545-07    | IV                      |
| Thermal shock resistance             | EN ISO 10545-09   | It stands the test      |
| Cracking resistance                  | EN ISO 10545-11   | It stands the test      |
| Frost resistance                     | EN ISO 10545-12   | It stands the test      |
|                                      |                   |                         |

| CHEMICAL PROPERTIES                                    |                 |     |
|--|-----------------|-----|
| Resistance to acids                                    | EN ISO 10545-13 | GLA |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLA |
| Resistance to cleaning products                        | EN ISO 10545-13 | GA  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |









# **ALPI GREEN POL RECT 29,5X29,5**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A037443** 29,5x29,5 10,00 PC BIA GL



#### **DIMENSIONS AND SURFACE PROPERTIES**

|                                      | PHYSICAL PROPERTIES |                         |
|--------------------------------------|---------------------|-------------------------|
| Water absorption capacity            | EN ISO 10545-03     | < 0,5%                  |
| Flexion resistance                   | EN ISO 10545-04     | => 45 N/mm <sup>2</sup> |
| Abrasion resistance (glazed Ceramic) | EN ISO10545-07      | IV                      |
| Thermal shock resistance             | EN ISO 10545-09     | It stands the test      |
| Cracking resistance                  | EN ISO 10545-11     | It stands the test      |
| Frost resistance                     | EN ISO 10545-12     | It stands the test      |

| CHEMICAL PROPERTIES                                    |                 |     |  |
|--|-----------------|-----|--|
| Resistance to acids                                    | EN ISO 10545-13 | GLA |  |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLA |  |
| Resistance to cleaning products                        | EN ISO 10545-13 | GA  |  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA  |  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |  |









# **ALPI GREEN POL RECT 14,5X14,5**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A037444** 14,5X14,5 9,80 PC BIA GL



#### **DIMENSIONS AND SURFACE PROPERTIES**

|                                      | PHYSICAL PROPERTIES |                       |
|--------------------------------------|---------------------|-----------------------|
| Water absorption capacity            | EN ISO 10545-03     | < 0,5%                |
| Flexion resistance                   | EN ISO 10545-04     | $=>45 \text{ N/mm}^2$ |
| Abrasion resistance (glazed Ceramic) | EN ISO10545-07      | IV                    |
| Thermal shock resistance             | EN ISO 10545-09     | It stands the test    |
| Cracking resistance                  | EN ISO 10545-11     | It stands the test    |
| Frost resistance                     | EN ISO 10545-12     | It stands the test    |

| CHEMICAL PROPERTIES                                    |                 |     |  |
|--|-----------------|-----|--|
| Resistance to acids                                    | EN ISO 10545-13 | GLA |  |
| Resistance to alcalis                                  | EN ISO 10545-13 | GLA |  |
| Resistance to cleaning products                        | EN ISO 10545-13 | GA  |  |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA  |  |
| Stains resistance                                      | EN ISO 10545-14 | 5   |  |










# LAVABO DE PIE ROMA

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040867** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# LAVABO NISO DCHA.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040866** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# LAVABO NISO IZQ.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040865** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# LAVABO AXEL CEN.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040870** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# LAVABO AXEL DCHA.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040869** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# LAVABO AXEL IZQ.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040868** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# **LAVABO AXEL DOBLE 160**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040871** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










### LAVABO ENEA CEN.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040874** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










### LAVABO ENEA DCHA.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040873** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# LAVABO ENEA IZQ.

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040872** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test










# **LAVABO ENEA DOBLE 160**

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

**A040875** 0,00 PC BIA GL



### **DIMENSIONS AND SURFACE PROPERTIES**

#### **PHYSICAL PROPERTIES**

Frost resistance EN ISO 10545-12 It stands the test





