

AUTHENTIC BARLEY RECT 25X150

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A042033 25x150 8,70 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test









ANTI-SLIP AUTHENTIC BARLEY RECT 25X150

REFERENCE SIZE (cm) THICKNESS (mm)

A042038 25x150 8,50 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

GROUP

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test

CHEMICAL PROPERTIES

ANTI-SLIP CHARACTERISTICS

Slip resistance (Rd) UNE-EN 16165-C Class 3

Slip resistance (R) EN 16165-B R11









AUTHENTIC SANDAL RECT 25X150

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A042031 25x150 8,50 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test









ANTI-SLIP AUTHENTIC SANDAL RECT 25X150

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A042036 25x150 8,90 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test

CHEMICAL PROPERTIES

ANTI-SLIP CHARACTERISTICS

Slip resistance (Rd) UNE-EN 16165-C Class 3

Slip resistance (R) EN 16165-B R11









AUTHENTIC ROMAN RECT 25X150

REFERENCE THICKNESS (mm) SIZE (cm) **GROUP**

PC BIA GL A042034 25x150 8,80



PHYSICAL PROPERTIES

EN ISO 10545-12 Frost resistance It stands the test









AUTHENTIC OAT RECT 25X150

REFERENCE SIZE (cm) THICKNESS (mm) GROUP

A042032 25x150 8,40 PC BIA GL



DIMENSIONS AND SURFACE PROPERTIES

PHYSICAL PROPERTIES

Frost resistance EN ISO 10545-12 It stands the test





