



Technical characteristics report

Serial: SENSATION	Size: 25x40
-------------------	-------------

Wall tiles with red body. Dry pressed ceramic tiles for interior walls.

It accomplishes norm: UNE-EN 14411

Group: BIII

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	> 10 %
Flexion resistance	EN ISO 10545-04	> 22 N/mm ²
Hardness degree, method MOHS	UNE 67-101-92	≥ 3
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

Technical characteristics report

Serial: Sensation	Size: 31.6x31.6
-------------------	-----------------

SENSATION WHITE

Floor tiles with red body. Dry pressed ceramic tiles for interior floors and walls.

It accomplishes norm: UNE-EN 14411

Group: B1la

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$3\% < E \leq 6\%$
Flexion resistance	EN ISO 10545-04	$> 22 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV (2100 rev)
Hardness degree, method MOHS	UNE 67-101-92	≥ 6
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5

Technical characteristics report

Serial: Sensation	Size: 31.6x31.6
-------------------	-----------------

SENSATION NIGHT

Floor tiles with red body. Dry pressed ceramic tiles for interior floors and walls.

It accomplishes norm: UNE-EN 14411

Group: BIIa

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	$3\% < E \leq 6\%$
Flexion resistance	EN ISO 10545-04	$> 22 \text{ N/mm}^2$
Resistance to the abrasion, method PEI	EN ISO 10545-07	II (600 rev)
Hardness degree, method MOHS	UNE 67-101-92	≥ 4
Thermic impact resistance	EN ISO 10545-9	It stands the test
Cracking resistance	EN ISO 10545-11	It stands the test
Resistance to acids	EN ISO 10545-13	GHA
Resistance to bases	EN ISO 10545-13	GHA
Resistance to cleaning products and chemical products for swimming pool water	EN ISO 10545-13	GA
Stains resistance	EN ISO 10545-14	5