



Technical characteristics report

Serial: HOLLYWOOD

Size: 45X45

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

HOLLYWOOD GREY - BEIGE

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 38 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV
Thermal shock resistance	EN ISO 10545-9	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA/GHA
Resistance to alcalis	EN ISO 10545-13	GLA/GHA
Stains resistance	EN ISO 10545-14	5
Slip Resistance	UNE-ENV 12633	CLASS 1

QUALITY DEPARTMENT



Technical characteristics report

Serial: HOLLYWOOD

Size: 45X45

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

HOLLYWOOD CINDER – GRAPHITE - TORTOLA

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 38 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	III
Thermal shock resistance	EN ISO 10545-9	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA/GHA
Resistance to alcalis	EN ISO 10545-13	GLA/GHA
Stains resistance	EN ISO 10545-14	5
Slip Resistance	UNE-ENV 12633	CLASS 1

QUALITY DEPARTMENT



Technical characteristics report

Serial: HOLLYWOOD

Size: 30x60

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

BEL AIR GREY - BEIGE

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 38 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	IV
Thermal shock resistance	EN ISO 10545-9	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA/GHA
Resistance to alcalis	EN ISO 10545-13	GLA/GHA
Stains resistance	EN ISO 10545-14	5
Slip Resistance	UNE-ENV 12633	CLASS 1
Slip Resistance	DIN51130:2010 Apdo. 5 RAMPA	R9

QUALITY DEPARTMENT



Technical characteristics report

Serial: HOLLYWOOD

Size: 30x60

Gres Porcelain

Norm: UNE-EN 14411

Group: Bla

BEL AIR CINDER

Name, Test	European norm	Value
Size, thickness, side straightness, flatness, orthogonality	UNE-EN 14411	It accomplishes all requirements
Water absorption capacity	EN ISO 10545-03	< 0,5%
Flexion resistance	EN ISO 10545-04	> 38 N/mm ²
Resistance to the abrasion, method PEI	EN ISO 10545-07	III
Thermal shock resistance	EN ISO 10545-9	It stands the test
Frost resistance	EN ISO 10545-12	It stands the test
Resistance to acids	EN ISO 10545-13	GLA/GHA
Resistance to alcalis	EN ISO 10545-13	GLA/GHA
Stains resistance	EN ISO 10545-14	5
Slip Resistance	UNE-ENV 12633	CLASS 1
Slip Resistance	DIN51130:2010 Apdo. 5 RAMPA	R9

QUALITY DEPARTMENT